VersaPro® 96% AFUE GAS FURNACE

MGM96EE*****NB



- ✓ 96% AFUE
- ✓ Quiet Operation
- ✓ Superior Performance
- ✓ Durable Build & Finish
- ✓ Included LP Kit
- ✓ Multi-Position
- ✓ Two Stage
- ✓ Energy Efficient
- ✓ Compact Design

Upflow and horizontal flow. R-454B refrigerant leakage sensor adaptable.

SCAN HERE for the most up-to-date version of this brochure.

LIFETIME HEAT EXCHANGER WARRANTY

10 YEAR PARTS WARRANTY ★ 10 YEAR ★ GUARANTEED

48 Remington Way
Hickory, KY 42051
270.366.0457

www.mrcool.com

Version Date: 06-24-2025

VersaPro® 96% AFUE
GAS FURNACE‡ MGM96EE*****NB



Tough Winters? No Problem.

The MRCOOL® VersaPro® 96% AFUE Gas Furnace delivers quiet, high-efficiency performance—even in harsh conditions. Its two-stage DC motor and advanced heat exchangers (aluminized steel primary, stainless steel secondary) offer long-lasting reliability and energy savings.

Compact and versatile, it supports multi-position (upflow/horizontal) installation with flexible gas/electric connections and an easy-to-remove bottom panel for simplified service. Propane conversion is quick with an optional LP kit.

AHRI certified and ETL listed, VersaPro™ meets top industry standards. Register within 90 days for a 10-year parts and lifetime heat exchanger warranty—or get 5/20-year coverage by default.

VersaPro® — Built for Comfort. Backed for Life.

UPFLOW HORIZONTAL		Unit	MGM96EE060B3NB	MGM96EE080B3NB	MGM96EE080C4NB	MGM96EE100C5NB	MGM96EE120D5NB
PERFORMANCE							
Power Supply		V-Hz, Ph	115-60, 1	115-60, 1	115-60, 1	115-60, 1	115-60, 1
Natural Gas / LP	Input	Btu/h	60,000	80,000	80,000	100,000	120,000
	Output	Btu/h	57,000	76,000	76,000	95,000	115,000
Temp. Rise Range		°F	30-60	35-65	35-65	35-65	40-70
ELECTRICAL							
Min. / Max. Voltage		V	104/127	104/127	104/127	104/127	104/127
Min. Circuit Ampacity		A	8	8	7.8	11.5	10.5
Miax. Overcurrent Protection		A	15	15	15	20	20
DIMENSIONS & WEIGHT							
Cabinet Size (WxDxH)		inch	17.5 x 28.75 x 33.75	17.5 x 28.75 x 33.75	21 x 28.75 x 33.75	21 x 28.75 x 33.75	24.5 x 28.75 x 33.75
Packing Size (WxDxH)		inch	20 x 31.02 x 40.35	20 x 31.02 x 40.35	23.54 x 31.02 x 40.35	23.54 x 31.02 x 40.35	27.05 x 31.02 x 40.35
Net Weight		lbs	135	141	152	162	176
Gross Weight		lbs	147.5	153	165	173	190
FAN MOTOR							
Horsepower		HP	3/4	3/4	3/4	1	1
Max CFM @ 0.5ESP		CFM	1321	1214	1289	1774	1916
Motor Speeds			5 speed	5 speed	5 speed	5 speed	5 speed
CIRCULATOR BLOWER							
Material			Metal	Metal	Metal	Metal	Metal
Size		inch	12.375 x 8	12.375 x 8	12.75 x 11.25	12.75 x 11.25	12.75 x 11.25
Vent Diameter		inch	2"/3"	2"/3"	2"/3"	2"/3"	3"
No. of Burners			3	4	4	5	6
GAS							
Gas Type			NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)	NG (LP w/kit)
Gas Connection Size		inch	1/2	1/2	1/2	1/2	1/2
REBATE SUMMARY							
CEE Tier 2			✔	✔	✔	✔	✔

AHRI CERTIFIED® www.ahridirectory.org
Data provided by AHRI

c UL us LISTED

c ETL us Intertek

‡Registered Warranty provides for a total of 10 years of limited warranty coverage (Standard 5-year limited parts warranty plus an additional 5-year limited extended parts warranty; Lifetime heat exchanger warranty when registered). Warranty must be registered online within 60 days of installation to qualify for extended coverage. Unregistered equipment defaults to 5-year coverage.